



**10  
GPM**

101147H

**1.0 HP**

**DEEP WELL  
SUBMERSIBLE PUMP**

**Pumps up to 885 US GPH  
Maximum Head of 400 Feet**

**2 WIRE + GROUND / 230V  
15 STAGES**

**PUMP CAPACITY**

HEAD	LPH	US GPH
400' 122,0m	910	240
350' 106,0m	1780	470
325' 99,0m	2065	545
300' 91,0m	2270	600
275' 84,0m	2460	650
250' 76,0m	2630	695
225' 68,5m	2800	740
200' 61,0m	2990	790
180' 55,0m	3125	825
160' 49,0m	3255	860
140' 43,0m	3350	885

Friction loss in pipe not included

**Best efficiency**

Pressure switch set to :	Depth :
20/40 PSI	156' - 267'
30/50 PSI	133' - 244'



- Made of non-corrosive 316 stainless steel material
- Precision machined stainless steel impellers and diffusers
- NEMA standard stainless steel interchangeable pump head
- Hexagonal stainless steel drive shaft

**Recommended for homes,  
cottages and farms for installation  
in water wells which are 4" and  
larger in diameter.**



**Water in  
PUMP SYSTEM**

[www.burcam.com](http://www.burcam.com)

