

101157H

1.5 HP

**DEEP WELL
SUBMERSIBLE PUMP**

**Pumps up to 2030 US GPH
Maximum Head of 250 Feet**



**3 WIRE + GROUND / 230V
9 STAGES**

**25
GPM**

PUMP CAPACITY

| HEAD | | LPH | US GPH |
|------|-------|------|--------|
| 250' | 76,0m | 1875 | 495 |
| 225' | 68,5m | 3560 | 940 |
| 200' | 61,0m | 5150 | 1360 |
| 180' | 55,0m | 5905 | 1560 |
| 160' | 49,0m | 6660 | 1760 |
| 140' | 43,0m | 7155 | 1890 |
| 120' | 36,5m | 7685 | 2030 |

Friction loss in pipe not included

Best efficiency

| Pressure switch set to : | Depth : |
|--------------------------|------------|
| 20/40 PSI | 85' - 122' |
| 30/50 PSI | 62' - 99' |



- Made of non-corrosive 316 stainless steel material
- Precision machined stainless steel impellers and diffusers
- NEMA standard stainless steel interchangeable pump head
- Hexagonal stainless steel drive shaft

Recommended for homes, cottages and farms for installation in water wells which are 4'' or larger in diameter.

Control box included.



Water in
PUMP SYSTEM

