



**10  
GPM**



101165H

**2.0 HP**

**DEEP WELL  
SUBMERSIBLE PUMP**

**Pumps up to 880 US GPH  
Maximum Head of 700 Feet**

**3 WIRE + GROUND / 230V  
27 STAGES**

**PUMP CAPACITY**

HEAD	LPH	US GPH
700' 213,5m	1135	300
650' 198,0m	1590	420
600' 183,0m	1990	525
550' 167,5m	2160	570
500' 152,5m	2425	640
450' 137,0m	2610	690
400' 122,0m	2800	740
350' 106,0m	3010	795
325' 99,0m	3105	820
300' 91,0m	3200	845
275' 84,0m	3275	865
250' 76,0m	3330	880

Friction loss in pipe not included

**Best efficiency**

Pressure switch set to :	Depth :
20/40 PSI	313' - 545'
30/50 PSI	290' - 522'

- Made of non-corrosive 316 stainless steel material
- Precision machined stainless steel impellers and diffusers
- NEMA standard stainless steel interchangeable pump head
- Hexagonal stainless steel drive shaft

**Recommended for homes,  
cottages and farms for installation  
in water wells which are 4" or  
larger in diameter.**

**Control box included.**



**Water in  
PUMP SYSTEM**

[www.burcam.com](http://www.burcam.com)

