

105125H

1/2 HP

**DEEP WELL  
SUBMERSIBLE PUMP**

**Pumps up to 520 US GPH  
Maximum Head of 325 Feet**

**3 WIRE + GROUND / 115V  
13 STAGES**

**5  
GPM**

### PUMP CAPACITY

HEAD	LPH	US GPH
325' 99,0m	285	75
300' 91,0m	760	200
275' 84,0m	1060	280
250' 76,0m	1210	320
225' 68,5m	1365	360
200' 61,0m	1515	400
180' 55,0m	1590	420
160' 49,0m	1665	440
140' 43,0m	1740	460
120' 36,5m	1820	480
100' 30,5m	1895	500
80' 24,5m	1970	520

Friction loss in pipe not included

### Best efficiency

Pressure switch set to :	Depth :
20/40 PSI	126' - 191'
30/50 PSI	103' - 168'



- Made of non-corrosive 304 stainless steel material
- Precision machined Noryl impellers and diffusers
- NEMA standard stainless steel interchangeable pump head
- Stainless steel shell and drive shaft

**Recommended for homes, cottages and farms for installation in water wells which are 4" and larger in diameter.**

**Control box included.**



Water in  
PUMP SYSTEM

[www.burcam.com](http://www.burcam.com)

