

105143H

# 3/4 HP

**DEEP WELL  
SUBMERSIBLE PUMP**

**Pumps up to 580 US GPH  
Maximum Head of 350 Feet**

**3 WIRE + GROUND / 230V  
13 STAGES**

# 7 GPM

## PUMP CAPACITY

HEAD	LPH	US GPH
350' 106,5m	680	180
325' 99,0m	1040	275
300' 91,0m	1325	350
275' 84,0m	1475	390
250' 76,0m	1630	430
225' 68,5m	1780	470
200' 61,0m	1895	500
180' 55,0m	1950	515
160' 49,0m	2005	530
140' 43,0m	2080	550
120' 36,5m	2120	560
100' 30,5m	2160	570
80' 24,5m	2195	580

Friction loss in pipe not included

## Best efficiency

Pressure switch set to :	Depth :
20/40 PSI	85' - 205'
30/50 PSI	62' - 182'



- Made of non-corrosive 304 stainless steel material
- Precision machined Noryl impellers and diffusers
- NEMA standard stainless steel interchangeable pump head
- Stainless steel shell and drive shaft

**Recommended for homes, cottages and farms for installation in water wells which are 4" and larger in diameter.**

**Control box included.**



Water in  
PUMP SYSTEM

[www.burcam.com](http://www.burcam.com)

