

105155H

1.5 HP

**DEEP WELL
SUBMERSIBLE PUMP**

**Pumps up to 930 US GPH
Maximum Head of 500 Feet**

**3 WIRE + GROUND / 230V
15 STAGES**

**10
GPM**

PUMP CAPACITY

HEAD	LPH	US GPH
500' 152,5m	870	230
450' 137,0m	1365	360
400' 122,0m	1740	460
350' 106,0m	2005	530
325' 99,0m	2235	590
300' 91,0m	2440	645
275' 84,0m	2610	690
250' 76,0m	2765	730
225' 68,5m	2955	780
200' 61,0m	3105	820
180' 55,0m	3255	860
160' 49,0m	3405	900
140' 43,0m	3520	930

Friction loss in pipe not included

Best efficiency

Pressure switch set to :	Depth :
20/40 PSI	166' - 311'
30/50 PSI	143' - 288'



- Made of non-corrosive 304 stainless steel material
- Precision machined Noryl impellers and diffusers
- NEMA standard stainless steel interchangeable pump head
- Stainless steel shell and drive shaft

**Recommended for homes,
cottages and farms for installation
in water wells which are 4" and
larger in diameter.**

Control box included.



Water in
PUMP SYSTEM

www.burcam.com

