

Noryl pump body and ejector to prevent rust contamination.





- 1 1/4" suction

- 1" discharge

506732P

NORYL CONVERTIBLE JET PUMP WITH

Shallow Well Deep Well

Pumps up to: 800 US GPH 675 US GPH

Maximum vertical: 25 Feet 80 Feet suction lift

ELECTRONIC CONTROL

State of the art Deep Well Jet Pump



Convertible Jet Pump with electronic control

PUMP CAPACITY

| | LIFT | | LPH | US GPH |
|---------------------|------------------------------------|-------|------|--------|
| Deep Well Operation | | | | |
| | 80' | 24,5m | 475 | 125 |
| | 70' | 21,0m | 750 | 200 |
| | 30' | 9,0m | 2550 | 675 |
| | Shallow Well Operation | | | |
| | 25' | 7,5m | 1135 | 300 |
| | 5' | 1,5m | 3025 | 800 |
| | Friction loss in pipe not included | | | |

The electronic control PREVENTS THE PUMP from running dry and also offers other features

DESCRIPTION

- No need for a pressure switch and pressure tank.
- Noryl pump body.
- 115V (9.0A) motor, totally enclosed fan-cooled.
- Bearing to bearing stainless steel motor shaft.
- Full-time running capacitor.
- Stainless steel mechanical seal.

OPERATION

WARRANTY

- The electronic control turns the pump on instantly, when a tap is opened.
- When all taps are closed, the electronic control turns the pump off.



