




101161H

1/2 HP

DEEP WELL
SUBMERSIBLE PUMP

Pumps up to 890 US GPH
Maximum Head of 225 Feet

10
GPM



2 WIRE + GROUND / 230V
9 STAGES

PUMP CAPACITY

HEAD		LPH	US GPH
225'	68,5m	1380	365
200'	61,0m	1990	525
180'	55,0m	2250	595
160'	49,0m	2500	660
140'	43,0m	2725	720
120'	36,5m	2970	785
100'	30,5m	3180	840
80'	24,5m	3370	890

Friction loss in pipe not included

Best efficiency

Pressure switch set to :	Depth :
20/40 PSI	73' - 123'
30/50 PSI	50' - 100'



- Made of non-corrosive 316 stainless steel material
- Precision machined stainless steel impellers and diffusers
- NEMA standard stainless steel interchangeable pump head
- Hexagonal stainless steel drive shaft

Recommended for homes, cottages and farms for installation in water wells which are 4" and larger in diameter.

Complete sub-pack.



Water in
PUMP SYSTEM

www.burcam.com



**10
GPM**



**2 FILS + MISE À TERRE / 230V
9 ÉTAGES**

CAPACITÉ DE LA POMPE

TÊTE	LPH	GPH US
225'	68,5m	1380
200'	61,0m	1990
180'	55,0m	2250
160'	49,0m	2500
140'	43,0m	2725
120'	36,5m	2970
100'	30,5m	3180
80'	24,5m	3370

Pertes dues à la friction non incluses

Plage d'efficacité

Interrupteur à pression réglé à :	Profondeur :
20/40 LBS/PO ²	73' - 123'
30/50 LBS/PO ²	50' - 100'



- Fabriquée en acier inoxydable 316 non corrosif
- Impulseurs et diffuseurs en acier inoxydable usinés avec précision
- Tête de pompe interchangeable (standard NEMA)
- Arbre de moteur hexagonal en acier inoxydable

Recommandée pour la maison, le chalet et la ferme pour une installation dans un puits profond de 4" et plus de diamètre.

Ensemble sub-pack.

