



400417T

# 1.0 HP

## GRINDER PUMP FOR SEWAGE

**Pumps up to 7650 US GPH  
Maximum Head of 35 Feet**



**Pro series**  
for heavy duty

### PUMP CAPACITY

HEAD	LPH	US GPH
35' 10,5m	7500	2000
30' 9,0m	14900	3900
25' 7,5m	18200	4800
20' 6,0m	21000	5600
15' 4,5m	22000	5800
10' 3,0m	26000	6900
5' 1,5m	29000	7650

Friction loss in pipe not included



**Automatic  
On - Off  
OPERATION**

- Made of rugged cast iron and stainless steel for longevity
- Cast iron vortex impeller
- 2" discharge
- Switch sold separately, model 450478 (10') 230V
- Oil-cooled motor
- 20' electrical cords

**Replaces sewage pumps and designed for a permanent installation in a sewage basin.**



Water out  
PUMP SYSTEM

[www.burcam.com](http://www.burcam.com)



1.0 cv

**POMPE BROYEUSE  
POUR ÉGOUT****Pompe jusqu'à 29000 LPH  
Refoulement maximal  
de 10,5 mètres****Série professionnelle  
pour un rendement supérieur****CAPACITÉ DE LA POMPE**

TÊTE	LPH	GPH	US
35' 10,5m	7500	2000	
30' 9,0m	14900	3900	
25' 7,5m	18200	4800	
20' 6,0m	21000	5600	
15' 4,5m	22000	5800	
10' 3,0m	26000	6900	
5' 1,5m	29000	7650	

Pertes dues à la friction non incluses

**Fonctionnement  
Départ - Arrêt  
AUTOMATIQUE**

- Fabriquée de fonte robuste et d'acier inoxydable pour une durabilité accrue
- Impulseur vortex en fonte
- Décharge de 2"
- Flotte vendue séparément, modèle 450478 (10') 230V
- Moteur refroidi à l'huile
- Câbles électriques de 6m

**Remplace les pompes d'égout  
et est conçu pour une installation  
permanente dans un bassin d'égout.****Évacuation d'eau  
SYSTÈME DE POMPAGE**[www.burcam.com](http://www.burcam.com)