



400423T

# 3/4 HP

## COMPLETE GRINDER PUMP KIT

Pumps up to 1875 US GPH  
Maximum Head of 35 Feet



**18" x 30" BASIN**  
(Overall dimension : 21 1/2" x 32 1/4")

### PUMP CAPACITY

HEAD	LPH	US GPH
35' 10,5m	1900	500
30' 9,0m	4200	1100
20' 6,0m	6200	1635
10' 3,0m	7100	1875

Friction loss in pipe not included



**"AQUAFLEX"**  
gaskets & seals

- Basin : - Heavy duty polyethylene
- Non-corrosive cover
- Pump : - Made of rugged cast iron
- Prevent maintenance and clogged pipes
- Discharge adaptor of 2"
- Oil-cooled motor
- 8' electrical cord

**New grinding technology for sewage application, to grind solids.**



Water out  
PUMP SYSTEM

[www.burcam.com](http://www.burcam.com)





400423T

# 3/4 CV

## SYSTÈME DE POMPE BROYEUSE POUR ÉGOUT

Pompe jusqu'à 7100 LPH  
Refoulement maximal  
de 10,5 mètres



**BASSIN 18" x 30"**  
(Dimension globale : 21 1/2" x 32 1/4")

### CAPACITÉ DE LA POMPE

TÊTE	LPH	GPH US
------	-----	--------

35' 10,5m	1900	500
30' 9,0m	4200	1100
20' 6,0m	6200	1635
10' 3,0m	7100	1875

Pertes dues à la friction non incluses



**Joint d'étanchéité  
"AQUAFLEX"**

- Bassin :**
- Robuste, fait de polyéthylène
  - Couvercle anti-corrosion
- Pompe :**
- Fabriquée de fonte robuste
  - Préviend l'entretien et l'obstruction des tuyaux
  - Adaptateur de décharge de 2"
  - Moteur refroidi à l'huile
  - Câbles électriques de 2.4m

**Nouvelle technologie de déchetage pour application d'égout pour éliminer les solides.**



Évacuation d'eau  
SYSTÈME DE POMPAGE

[www.burcam.com](http://www.burcam.com)

