



506227P

3/4 HP

SHALLOW WELL JET PUMP

Pumps up to 850 US GPH
Maximum vertical suction lift of 25 Feet



PUMP CAPACITY

| LIFT | | LPH | US GPH |
|------|------|------|--------|
| 25' | 7,5m | 1600 | 425 |
| 20' | 6,0m | 1815 | 480 |
| 15' | 4,5m | 2535 | 670 |
| 10' | 3,0m | 2875 | 760 |
| 5' | 1,5m | 3220 | 850 |

Friction loss in pipe not included

- 1 1/4" suction
- 1" discharge



Recommended for
home, cottage and
farm applications

- Easy to prime large pump body
- Totally enclosed fan-cooled motor 115/230V, 60Hz, bearing to bearing stainless steel motor shaft, with automatic thermal and overload protection, and full-time run capacitor
- Stainless steel mechanical seal
- 7 US gallon steel air pressure tank
- No water-air contact
- No water-tank contact

Noryl pump body to prevent accumulation of rust.



Water in
PUMP SYSTEM

www.burcam.com



3/4 CV

POMPE À JET DE Puits DE SURFACE

Pompe jusqu'à 3220 LPH

Aspiration verticale maximale
de 7,5 mètres



CAPACITÉ DE LA POMPE

| ÉLEVATION | LPH | GPH | US |
|-----------|-----|-----|----|
|-----------|-----|-----|----|

| | | |
|----------|------|-----|
| 25' 7,5m | 1600 | 425 |
| 20' 6,0m | 1815 | 480 |
| 15' 4,5m | 2535 | 670 |
| 10' 3,0m | 2875 | 760 |
| 5' 1,5m | 3220 | 850 |

Pertes dues à la friction non incluses.



- Aspiration de 1 1/4"
- Décharge de 1"



Recommandée pour
la maison, le chalet
ou la ferme

- Moteur 115/230V, fermé et refroidi par un ventilateur
- Arbre du moteur en acier inoxydable, sur roulement à billes
- Sceau mécanique en acier inoxydable
- Comprend un réservoir de 25 L
- Aucun contact de l'eau avec air
- Aucun contact de l'eau avec le réservoir

Boîtier de pompe en Noryl
pour prévenir la contamination
par la corrosion.



Approvisionnement d'eau
SYSTÈME DE POMPAGE

www.burcam.com

