



Noryl pump body and ejector to prevent rust contamination.



- 1 1/4" suction
- 1" discharge



506728PSS

3/4 HP

NORYL CONVERTIBLE JET PUMP SYSTEM

	Shallow Well	Deep Well
Pumps up to :	800 US GPH	675 US GPH
Maximum vertical suction lift :	25 Feet	80 Feet



PUMP CAPACITY

LIFT		LPH	US GPH
Deep Well Operation			
80'	24,5m	475	125
70'	21,0m	750	200
30'	9,0m	2550	675
Shallow Well Operation			
25'	7,5m	1135	300
5'	1,5m	3025	800

Friction loss in pipe not included

Recommended for home, cottage and farm applications

DESCRIPTION

- 16 US gallon stainless steel air pressure tank
- No water-air contact
- No water-tank contact
- Noryl pump body.
- 115/230V (9.0/4.5A) motor, totally enclosed fan-cooled.
- Bearing to bearing stainless steel motor shaft.
- Full-time running capacitor.
- Stainless steel mechanical seal.

OPERATION

- In conjunction with a pressure tank, the pressure switch turns the pump on when the pressure drops below 30 PSI and turns the pump off when the pressure rises up to 50 PSI.



Water in PUMP SYSTEM

www.burcam.com



**Boîtier de pompe et éjecteur
en Noryl pour prévenir la
contamination par la corrosion.**



- Aspiration de 1 1/4"
- Décharge de 1"



506728PSS

3/4 cv

**SYSTÈME DE POMPE À JET
CONVERTIBLE EN NORYL**

	Puits de surface	Puits profond
Pompe jusqu'à :	3025 LPH	2550 LPH
Aspiration verticale maximale :	7,5 mètres	24,5 mètres



CAPACITÉ DE LA POMPE

ÉLÉVATION	LPH	US GPH
Opération de puits profond		
80' 24,5m	475	125
70' 21,0m	750	200
30' 9,0m	2550	675
Opération de puits de surface		
25' 7,5m	1135	300
5' 1,5m	3025	800

Pertes dues à la friction non incluses

**Recommandée pour
la maison, le chalet
et la ferme**

DESCRIPTION

- Réservoir à air captif en acier inoxydable de 60L.
- Aucun contact de l'eau avec air.
- Aucun contact de l'eau avec le réservoir.
- Boîtier de pompe en Noryl.
- Moteur 115/230V (9.0/4.5A), fermé et refroidi par un ventilateur.
- Arbre du moteur en acier inoxydable, sur roulements à billes.
- Condensateur à fonction continue.
- Sceau mécanique en acier inoxydable.

FONCTIONNEMENT

- En conjonction avec un réservoir sous pression, l'interrupteur à pression démarre la pompe lorsque la pression baisse sous 30lbs/po² et arrête celle-ci lorsque la pression atteint 50lbs/po².



Approvisionnement d'eau
SYSTÈME DE POMPAGE

www.burcam.com

