



101162H

3/4 HP

DEEP WELL SUBMERSIBLE PUMP

Pumps up to 900 US GPH
Maximum Head of 275 Feet

10 GPM



2 WIRE + GROUND / 230V 12 STAGES

PUMP CAPACITY

| HEAD | | LPH | US GPH |
|------|-------|------|--------|
| 275' | 84,0m | 1760 | 465 |
| 250' | 76,0m | 2180 | 575 |
| 225' | 68,5m | 2405 | 635 |
| 200' | 61,0m | 2615 | 690 |
| 180' | 55,0m | 2800 | 740 |
| 160' | 49,0m | 2975 | 785 |
| 140' | 43,0m | 3145 | 830 |
| 120' | 36,5m | 3295 | 870 |
| 100' | 30,5m | 3410 | 900 |

Friction loss in pipe not included



Best efficiency

| Pressure switch set to : | Depth : |
|--------------------------|-------------|
| 20/40 PSI | 114' - 198' |
| 30/50 PSI | 91' - 175' |

- Made of non-corrosive 316 stainless steel material
- Precision machined stainless steel impellers and diffusers
- NEMA standard stainless steel interchangeable pump head
- Hexagonal stainless steel drive shaft

Recommended for homes, cottages and farms for installation in water wells which are 4'' and larger in diameter.

Complete sub-pack.



Water in
PUMP SYSTEM

www.burcam.com



10
GPM



2 FILS + MISE À TERRE / 230V
12 ÉTAGES

CAPACITÉ DE LA POMPE

| | TÊTE | LPH | GPH US |
|------|-------|------|--------|
| 275' | 84,0m | 1760 | 465 |
| 250' | 76,0m | 2180 | 575 |
| 225' | 68,5m | 2405 | 635 |
| 200' | 61,0m | 2615 | 690 |
| 180' | 55,0m | 2800 | 740 |
| 160' | 49,0m | 2975 | 785 |
| 140' | 43,0m | 3145 | 830 |
| 120' | 36,5m | 3295 | 870 |
| 100' | 30,5m | 3410 | 900 |

Pertes dues à la friction non incluses



Plage d'efficacité

| Interrupteur à pression réglé à : | Profondeur : |
|-----------------------------------|--------------|
| 20/40 LBS/PO ² | 114' - 198' |
| 30/50 LBS/PO ² | 91' - 175' |

- Fabriquée en acier inoxydable 316 non corrosif
- Impulseurs et diffuseurs en acier inoxydable usinés avec précision
- Tête de pompe interchangeable (standard NEMA)
- Arbre de moteur hexagonal en acier inoxydable

Recommandée pour la maison, le chalet et la ferme pour une installation dans un puits profond de 4" et plus de diamètre.

Ensemble sub-pack.

