



506221P

3/4 HP

SHALLOW WELL JET PUMP

Pumps up to 850 US GPH
Maximum Vertical Suction Lift
of 25 Feet



PUMP CAPACITY

LIFT		LPH	US GPH
25'	7,5m	1600	425
20'	6,0m	1815	480
15'	4,5m	2535	670
10'	3,0m	2875	760
5'	1,5m	3220	850

Friction loss in pipe not included

- 1 1/4" suction
- 1" discharge



Recommended for
home, cottage and
farm applications

- Totally enclosed fan-cooled motor 115/230V, 60Hz, bearing to bearing stainless steel motor shaft, with automatic thermal and overload protection, and full-time run capacitor
- Stainless steel mechanical seal

Noryl pump body to prevent accumulation of rust.



Water in
PUMP SYSTEM

www.burcam.com



Pompe jusqu'à 3220 LPH

Aspiration verticale maximale
de 7,5 mètres**CAPACITÉ DE LA POMPE**
ÉLEVATION LPH GPH US

25'	7,5m	1600	425
20'	6,0m	1815	480
15'	4,5m	2535	670
10'	3,0m	2875	760
5'	1,5m	3220	850

Pertes dues à la friction non incluses.

- Aspiration de 1 1/4"
- Décharge de 1"

**Recommandée pour**
la maison, le chalet
et la ferme

- Moteur 115/230V, 60Hz, fermé et refroidi par un ventilateur. Arbre du moteur en acier inoxydable sur roulements à billes avec protection thermique et de surcharge automatique et condensateur à fonction continue
- Sceau mécanique en acier inoxydable

Boîtier de pompe en Noryl
pour prévenir la contamination
par la corrosion.