



506227PSS

3/4 HP

SHALLOW WELL JET PUMP

Pumps up to 850 US GPH
Maximum vertical suction lift of 25 Feet



PUMP CAPACITY

LIFT		LPH	US GPH
25'	7,5m	1600	425
20'	6,0m	1815	480
15'	4,5m	2535	670
10'	3,0m	2875	760
5'	1,5m	3220	850

Friction loss in pipe not included

- 1 1/4" suction
- 1" discharge



Recommended for
home, cottage and
farm applications

- Easy to prime large pump body
- 115/230V motor, totally enclosed fan-cooled
- Bearing to bearing stainless steel motor shaft
- Stainless steel mechanical seal
- 7 US gallon stainless steel pressure air tank
- No water-air contact
- No water-tank contact

Noryl pump body to prevent accumulation of rust.



Water in
PUMP SYSTEM

www.burcam.com



3/4 CV

**POMPE À JET
DE Puits DE SURFACE**

Pompe jusqu'à 3220 LPH

Aspiration verticale maximale
de 7,5 mètres**CAPACITÉ DE LA POMPE**
ÉLEVATION LPH GPH US

25'	7,5m	1600	425
20'	6,0m	1815	480
15'	4,5m	2535	670
10'	3,0m	2875	760
5'	1,5m	3220	850

Pertes dues à la friction non incluses.

- Aspiration de 1 1/4"
- Décharge de 1"

**Recommandé pour**
maison, cotation et
l'application agricole

- Moteur 115/230V, fermé et refroidi par un ventilateur
- Arbre du moteur en acier inoxydable, sur roulement à billes
- Sceau mécanique en acier inoxydable
- Réservoir de 25 L en acier inoxydable
- Aucun contact de l'eau avec air
- Aucun contact de l'eau avec le réservoir

Boîtier de pompe en Noryl
pour prévenir la contamination
par la corrosion.Approvisionnement d'eau
SYSTÈME DE POMPAGEwww.burcam.com