



506228PSS

3/4 HP

SHALLOW WELL JET PUMP

Pumps up to 850 US GPH
Maximum vertical suction lift of 25 Feet



PUMP CAPACITY

LIFT		LPH	US GPH
25'	7,5m	1600	425
20'	6,0m	1815	480
15'	4,5m	2535	670
10'	3,0m	2875	760
5'	1,5m	3220	850

Friction loss in pipe not included

- 1 1/4" suction
- 1" discharge



Recommended for
home, cottage and
farm applications

- Easy to prime large pump body
- 115/230V motor, totally enclosed fan-cooled
- Bearing to bearing stainless steel motor shaft
- Stainless steel mechanical seal
- 16 US gallon stainless steel pressure air tank
- No water-air contact
- No water-tank contact

Noryl pump body to prevent accumulation of rust.



Water in
PUMP SYSTEM

www.burcam.com





506228PSS

3/4 HP

SHALLOW WELL JET PUMP

Pumps up to 850 US GPH
Maximum vertical suction lift of 25 Feet



PUMP CAPACITY

LIFT		LPH	US GPH
25'	7,5m	1600	425
20'	6,0m	1815	480
15'	4,5m	2535	670
10'	3,0m	2875	760
5'	1,5m	3220	850

Friction loss in pipe not included

- 1 1/4" suction
- 1" discharge



Recommended for
home, cottage and
farm applications

- Easy to prime large pump body
- 115/230V motor, totally enclosed fan-cooled
- Bearing to bearing stainless steel motor shaft
- Stainless steel mechanical seal
- 16 US gallon stainless steel pressure air tank
- No water-air contact
- No water-tank contact

Noryl pump body to prevent accumulation of rust.



Water in
PUMP SYSTEM

www.burcam.com

