



506518SS

# 3/4 HP

## SHALLOW WELL JET PUMP

**Pumps up to 900 US GPH  
Maximum Suction Lift of 25 Feet**



### PUMP CAPACITY

LIFT		LPH	US GPH
25'	7,5m	1800	475
20'	6,0m	2100	560
15'	4,5m	2400	640
10'	3,0m	2800	750
5'	1,5m	3400	900

Friction loss in pipe not included



### Easy to PRIME

- Totally enclosed fan-cooled motor 115/230V, 60Hz, bearing to bearing
- Built-in ejector
- Full-time run capacitor
- Stainless steel mechanical seal

### Corrosion resistant stainless steel pump body.



Water in PUMP SYSTEM

[www.burcam.com](http://www.burcam.com)



**POMPE À JET  
DE Puits DE SURFACE**

Pompe jusqu'à 3400 LPH

Aspiration verticale maximale  
de 7,5 mètres**CAPACITÉ DE LA POMPE**  
ÉLÉVATION LPH GPH US

25'	7,5m	1800	475
20'	6,0m	2100	560
15'	4,5m	2400	640
10'	3,0m	2800	750
5'	1,5m	3400	900

Pertes dues à la friction non incluses

**Facile à  
AMORCER**

- Moteur 115/230V, 60Hz, fermé et refroidi par un ventilateur. Arbre de moteur en acier inoxydable sur roulements à billes
- Injecteur intégré
- Condensateur à fonction continue
- Sceau mécanique en acier inoxydable

**Boîtier de pompe en acier  
inoxydable pour prévenir la  
contamination par la corrosion.**Approvisionnement d'eau  
SYSTÈME DE POMPAGE[www.burcam.com](http://www.burcam.com)