



600546B

26 US GAL

### CAPTIVE AIR PRESSURE TANK



NPT Connection	1"	
Pressure switch set to	20/40	30/50
Precharge to	18 PSI	28 PSI
Drawdown	8.8 US GALLON	7.0 US GALLON

**Replaceable bladder. Made of butyl synthetic rubber to increase reliability and life span.**



- No water to metal contact, rust-free operation
- Flange made of stainless steel

**Designed for water systems assembled with a jet pump or a deep well submersible pump.**



Water in PUMP SYSTEM

[www.burcam.com](http://www.burcam.com)





600546B

100L

## RÉSERVOIR À AIR CAPTIF



Branchement NPT	1"	
Interrupteur à pression réglé à	20/40	30/50
Préchargé à	18 LBS PO <sup>2</sup>	28 LBS PO <sup>2</sup>
Soutirage	8.8 GALLON US	7.0 GALLON US

**Membrane remplaçable.  
Fabriquée en butyle  
synthétique pour  
augmenter la fiabilité  
et la durée de vie.**



- Aucun contact eau-métal, pour prévenir la corrosion
- Bride en acier inoxydable

**Conçu pour les systèmes d'eau  
assemblés avec une pompe à jet  
ou une pompe submersible de  
puits profond.**



Approvisionnement d'eau  
SYSTÈME DE POMPAGE

[www.burcam.com](http://www.burcam.com)

