



600652SS

16 US GAL

**HORIZONTAL CAPTIVE AIR PRESSURE TANK**



|                        |               |               |
|------------------------|---------------|---------------|
| NPT Connection         | 1"            |               |
| Pressure switch set to | 20/40         | 30/50         |
| Precharge to           | 18 PSI        | 28 PSI        |
| Drawdown               | 5.0 US GALLON | 4.0 US GALLON |

**Replaceable bladder. Made of butyl synthetic rubber to increase reliability and life span.**



**Stainless steel CONSTRUCTION**

- No water to metal contact, rust-free operation
- Flange made of stainless steel

**Designed for water systems assembled with a jet pump or a deep well submersible pump.**



Water in PUMP SYSTEM

[www.burcam.com](http://www.burcam.com)



60L

**RÉSERVOIR  
HORIZONTAL  
À AIR CAPTIF**

|                                 |                        |                        |
|---------------------------------|------------------------|------------------------|
| Branchement NPT                 | 1"                     |                        |
| Interrupteur à pression réglé à | 20/40                  | 30/50                  |
| Préchargé à                     | 18 LBS PO <sup>2</sup> | 28 LBS PO <sup>2</sup> |
| Soutirage                       | 5.0 GALLON US          | 4.0 GALLON US          |

**Membrane remplaçable.  
Fabriquée en butyle  
synthétique pour  
augmenter la fiabilité  
et la durée de vie.**



**FABRIQUÉ  
d'acier inoxydable**

- Aucun contact eau-métal, pour prévenir la corrosion
- Bride en acier inoxydable

**Conçu pour les systèmes d'eau  
assemblés avec une pompe à jet  
ou une pompe submersible de  
puits profond.**

