



300319B

1/4 HP

**AUTOMATIC UNDER SINK PUMP SYSTEM**

**Pumps up to 2800 US GPH  
Maximum Head of 18 Feet**



**Designed for a  
PERMANENT INSTALLATION**

**PUMP CAPACITY**

HEAD	LPH	US GPH
18' 5,5m	2275	600
15' 4,5m	6050	1600
10' 3,0m	8325	2200
5' 1,5m	10600	2800

Friction loss in pipe not included



- 115V, 60Hz motor, with thermal and overload protection
- Vertical float switch for automatic operation
- Accommodates 1 1/4" or 1 1/2" discharge pipe
- Heavy duty basin + lid made of non-corrosive polyethylene resin, (14 1/2" x 13 1/2").

**Designed to handle normal waste water not containing solids, from domestic sinks.**



**Water out  
PUMP SYSTEM**

[www.burcam.com](http://www.burcam.com)





Conçu pour une  
**INSTALLATION PERMANENTE**

**CAPACITÉ DE LA POMPE**

TÊTE	LPH	GPH	US
18' 5,5m	2275	600	
15' 4,5m	6050	1600	
10' 3,0m	8325	2200	
5' 1,5m	10600	2800	

Pertes dues à la friction non incluses



- Moteur 115V, 60Hz, avec protection thermique et de surcharge
- Interrupteur vertical pour opération automatique
- Convient aux tuyaux d'évacuation de 1 1/4" ou 1 1/2"
- Bassin et couvercle fabriqués en résine de polyéthylène, non corrosif (14 1/2" x 13 1/2").

**Conçu pour traiter les eaux usées  
ne contenant pas de solides,  
provenant des éviers domestiques.**



Évacuation d'eau  
SYSTÈME DE POMPAGE

