



300500Z

1/3 HP

SUBMERSIBLE SUMP PUMP

Pumps up to 3000 US GPH
Maximum Head of 18 Feet



ADDED VALUE !

Zinc plated motor housing
for longer motor life

PUMP CAPACITY

HEAD	LPH	US GPH
18' 5,5m	5500	1450
15' 4,5m	7800	2000
10' 3,0m	9500	2500
5' 1,5m	11350	3000

Friction loss in pipe not included



Ideal for residential
automatic drainage
of basement sump pits

- Reduces heat
- Stops premature rust
- 1 1/2" discharge with 1 1/4" reducer
- Oil-cooled motor
- 8' electrical cord

Replaces upright and submersible pumps and designed for a permanent installation in a 14" basin and larger.



Water out
PUMP SYSTEM

www.burcam.com





300500Z

1/3 CV

POMPE DE PUISARD SUBMERSIBLE

Pompe jusqu'à 11350 LPH
Refoulement maximal
de 5,5 mètres



VALEUR AJOUTÉE !

Boîtier du moteur plaqué
zinc pour une durabilité
accrue du moteur

CAPACITÉ DE LA POMPE

TÊTE	LPH	GPH	US
18' 5,5m	5500	1450	
15' 4,5m	7800	2000	
10' 3,0m	9500	2500	
5' 1,5m	11350	3000	

Pertes dues à la friction non incluses



Idéale pour un
drainage automatique
des puits de
sous-sol résidentiel

- Dissipe la chaleur
- Protège contre la corrosion prématurée
- Décharge de 1 1/2", adaptateur de 1 1/4"
- Moteur refroidi à l'huile
- Câbles électriques de 2.4m

Remplace les pompes submersibles
ou à colonne et est conçue pour
une installation permanente dans
un bassin de 14" et plus.



Évacuation d'eau
SYSTÈME DE POMPAGE

www.burcam.com

