



300526

1/2 HP

SUBMERSIBLE EFFLUENT PUMP

Pumps up to 4400 US GPH
Maximum Head of 25 Feet



Ideal for residential
automatic drainage
of basement sump pits

PUMP CAPACITY

HEAD		LPH	US GPH
25'	7,5m	2250	600
20'	6,0m	7750	2000
15'	4,5m	10200	2700
10'	3,0m	13600	3600
5'	1,5m	16600	4400

Friction loss in pipe not included

- PRO SERIES



1/2" solids HANDLING

- 1 1/2" discharge with 1 1/4" reducer
- Noryl vortex impeller, clog free type
- Water-cooled
- Stainless steel motor housing
- Cast iron base
- 8' electrical cord

Replaces upright and submersible pumps and designed for a permanent installation in a 10" basin and larger.



Water out
PUMP SYSTEM

www.burcam.com



**POMPE D'EFFLUENT
SUBMERSIBLE**

Pompe jusqu'à 16600 LPH
Refoulement maximal
de 7,5 mètres



Idéale pour un
drainage automatique
des puits de
sous-sol résidentiel

CAPACITÉ DE LA POMPE

TÊTE	LPH	GPH US
25' 7,5m	2250	600
20' 6,0m	7750	2000
15' 4,5m	10200	2700
10' 3,0m	13600	3600
5' 1,5m	16600	4400

Pertes dues à la friction non incluses



ACCEPTÉ
les solides
de 1/2"

- Décharge de 1 1/2", adaptateur de 1 1/4"
- Impulseur vortex, de type ouvert, fabriqué de Noryl
- Moteur refroidi à l'eau
- Boîtier du moteur en acier inoxydable
- Base en fonte
- Câble électrique de 2.4m

**Remplace les pompes submersibles
ou à colonne et est conçue pour
une installation permanente dans
un bassin de 10" et plus.**

