



300610Z

1/3 HP

SUBMERSIBLE SUMP PUMP

Pumps up to 3000 US GPH
Maximum Head of 18 Feet



ADDED VALUE !

Zinc plated motor housing for longer motor life

PUMP CAPACITY

HEAD		LPH	US GPH
18'	5,5m	5500	1450
15'	4,5m	7800	2000
10'	3,0m	9500	2500
5'	1,5m	11350	3000

Friction loss in pipe not included



Ideal for residential automatic drainage of basement sump pits

- Reduces heat
- Stops premature rust
- 1 1/2" discharge with 1 1/4" reducer
- Oil-cooled motor
- 8' electrical cord

Replaces upright and submersible pumps and designed for a permanent installation in a 10" basin and larger.



Water out
PUMP SYSTEM

www.burcam.com





300610Z

1/3 CV

POMPE DE PUISARD SUBMERSIBLE

Pompe jusqu'à 11350 LPH
Refoulement maximal
de 5,5 mètres



VALEUR AJOUTÉE !

Boîtier du moteur plaqué zinc pour une durabilité accrue du moteur

CAPACITÉ DE LA POMPE

TÊTE	LPH	GPH	US
18' 5,5m	5500	1450	
15' 4,5m	7800	2000	
10' 3,0m	9500	2500	
5' 1,5m	11350	3000	

Pertes dues à la friction non incluses



Idéale pour un drainage automatique des puits de sous-sol résidentiel

- Dissipe la chaleur
- Protège contre la corrosion prématurée
- Décharge de 1 1/2", adaptateur de 1 1/4"
- Moteur refroidi à l'huile
- Câble électrique de 2.4m

Remplace les pompes submersibles ou à colonne et est conçue pour une installation permanente dans un bassin de 10" et plus.



Évacuation d'eau
SYSTÈME DE POMPAGE

www.burcam.com

