



300622

1/2 HP

### SUBMERSIBLE EFFLUENT PUMP

Pumps up to 3300 US GPH  
Maximum Head of 15 Feet



Ideal for residential  
**automatic drainage**  
of basement sump pits

#### PUMP CAPACITY

HEAD		LPH	US GPH
15'	4,5m	1350	360
10'	3,0m	7200	1900
5'	1,5m	12500	3300

Friction loss in pipe not included



Handles  
**UP TO 3/4"**  
solids

- 1 1/2" discharge with 1 1/4" reducer
- Oil-cooled motor
- 8' electrical cord

Replaces upright and submersible pumps and designed for a permanent installation in a 10" basin and larger.



Water out  
PUMP SYSTEM

www.burcam.com



1/2 CV

**POMPE D'EFFLUENT  
SUBMERSIBLE****Pompe jusqu'à 12500 LPH  
Refoulement maximal  
de 4,5 mètres**

Idéale pour un  
**drainage automatique**  
des puits de sous-sol résidentiel

**CAPACITÉ DE LA POMPE**

TÊTE	LPH	GPH US
15' 4,5m	1350	360
10' 3,0m	7200	1900
5' 1,5m	12500	3300

Pertes dues à la friction non incluses

**Accepte  
les solides  
DE 3/4"**

- Décharge de 1 1/2", adaptateur de 1 1/4"
- Moteur refroidi à l'huile
- Câble électrique de 2.4m

**Remplace les pompes submersibles  
ou à colonne et est conçue pour  
une installation permanente dans  
un bassin de 10" et plus.**

**Évacuation d'eau**  
SYSTÈME DE POMPAGE[www.burcam.com](http://www.burcam.com)