



300780V

1/2 HP

### SUBMERSIBLE SUMP PUMP

Pumps up to 3000 US GPH  
Maximum Head of 25 Feet



#### PUMP CAPACITY

HEAD	LPH	US GPH
25' 7,5m	1325	350
20' 6,0m	2840	750
15' 4,5m	5300	1400
10' 3,0m	8325	2200
5' 1,5m	11350	3000

Friction loss in pipe not included



Ideal for residential automatic drainage of basement sump pits

- Made of rugged cast iron and non-corrosive Noryl
- 1 1/2" discharge with 1 1/4" reducer
- Oil-cooled motor
- 8' electrical cord

Replaces upright and submersible pumps and designed for a permanent installation in a 10" basin and larger.



Water out  
PUMP SYSTEM

www.burcam.com



1/2 CV

**POMPE DE PUISARD  
SUBMERSIBLE****Pompe jusqu'à 11350 LPH  
Refoulement maximal  
de 7,5 mètres****CAPACITÉ DE LA POMPE**

TÊTE	LPH	GPH US
25' 7,5m	1325	350
20' 6,0m	2840	750
15' 4,5m	5300	1400
10' 3,0m	8325	2200
5' 1,5m	11350	3000

Pertes dues à la friction non incluses

**Idéale pour un  
drainage automatique  
des puits de  
sous-sol résidentiel**

- Fabriquée de fonte robuste et Noryl non corrosif
- Décharge de 1 1/2", adaptateur de 1 1/4"
- Moteur refroidi à l'huile
- Câble électrique de 2.4m

**Remplace les pompes submersibles  
ou à colonne et est conçue pour  
une installation permanente dans  
un bassin de 14" et plus.****Évacuation d'eau  
SYSTÈME DE POMPAGE**[www.burcam.com](http://www.burcam.com)