



300781

1/2 HP

SUBMERSIBLE SUMP PUMP

Pumps up to 3000 US GPH
Maximum Head of 25 Feet



PUMP CAPACITY

HEAD	LPH	US GPH
25' 7,5m	1325	350
20' 6,0m	2840	750
15' 4,5m	5300	1400
10' 3,0m	8325	2200
5' 1,5m	11350	3000

Friction loss in pipe not included



Ideal for residential
automatic drainage
of basement sump pits

- Made of rugged cast iron and non-corrosive Noryl
- 1 1/2" discharge with 1 1/4" reducer
- Oil-cooled motor
- 8' electrical cord

Replaces upright and submersible pumps and designed for a permanent installation in a 14" basin and larger.



Water out
PUMP SYSTEM

www.burcam.com



1/2 CV

**POMPE DE PUISARD
SUBMERSIBLE****Pompe jusqu'à 11350 LPH
Refoulement maximal
de 7,5 mètres****CAPACITÉ DE LA POMPE**

TÊTE	LPH	GPH US
25' 7,5m	1325	350
20' 6,0m	2840	750
15' 4,5m	5300	1400
10' 3,0m	8325	2200
5' 1,5m	11350	3000

Pertes dues à la friction non incluses

**Idéale pour un
drainage automatique
des puits de
sous-sol résidentiel**

- Fabriquée de fonte robuste et Noryl non corrosif
- Décharge de 1 1/2", adaptateur de 1 1/4"
- Moteur refroidi à l'huile
- Câble électrique de 2.4m

**Remplace les pompes submersibles
ou à colonne et est conçue pour
une installation permanente dans
un bassin de 14" et plus.****Évacuation d'eau**
SYSTÈME DE POMPAGEwww.burcam.com