



300818Z

1/2 HP

### SUBMERSIBLE SUMP PUMP

Pumps up to 3250 US GPH  
Maximum Head of 22 Feet



Ideal for residential automatic drainage of basement sump pits

#### PUMP CAPACITY

HEAD	LPH	US GPH
22' 7,0m	1320	350
20' 6,0m	3500	925
15' 4,5m	5400	1425
10' 3,0m	8100	2140
5' 1,5m	12300	3250

Friction loss in pipe not included

- PRO SERIES



Automatic On - Off OPERATION

- 1 1/2" discharge with 1 1/4" reducer
- Oil-cooled motor
- 8' electrical cord

Replaces upright and submersible pumps and designed for a permanent installation in a 10" basin and larger.



Water out PUMP SYSTEM

www.burcam.com



# 1/2 CV

## POMPE DE PUISARD SUBMERSIBLE

Pompe jusqu'à 12300 LPH  
Refoulement maximal  
de 7,0 mètres

Idéale pour un  
**drainage automatique**  
des puits de  
sous-sol résidentiel



### CAPACITÉ DE LA POMPE

TÊTE	LPH	GPH US
22' 7,0m	1320	350
20' 6,0m	3500	925
15' 4,5m	5400	1425
10' 3,0m	8100	2140
5' 1,5m	12300	3250

Pertes dues à la friction non incluses.

- SERIE PROFESSIONNELLE



**Fonctionnement  
Départ - Arrêt  
AUTOMATIQUE**

- Décharge de 1 1/2" avec adaptateur 1 1/4"
- Moteur refroidi à l'huile
- Câble électrique de 2.4m

Remplace les pompes submersibles  
ou à colonne et est conçue pour  
une installation permanente dans  
un bassin de 10" et plus.



Évacuation d'eau  
SYSTÈME DE POMPAGE

[www.burcam.com](http://www.burcam.com)

