



300828Z

# 1/3 HP

## SUBMERSIBLE SUMP PUMP

Pumps up to 3050 US GPH  
Maximum Head of 18 Feet



Ideal for residential **automatic drainage** of basement sump pits

### PUMP CAPACITY

HEAD	LPH	US GPH
18' 5,5m	900	225
15' 4,5m	3475	925
10' 3,0m	7675	2025
5' 1,5m	11525	3050

Friction loss in pipe not included

**- PRO SERIES**



**Automatic  
On - Off  
OPERATION**

- Pump body made of rugged cast iron
- 1 1/2" discharge with 1 1/4" reducer
- Oil-cooled motor
- 8' electrical cord

**Replaces upright and submersible pumps and designed for a permanent installation in a 10" basin and larger.**



Water out  
PUMP SYSTEM

[www.burcam.com](http://www.burcam.com)



1/3 CV

**POMPE DE PUISARD  
SUBMERSIBLE****Pompe jusqu'à 11525 LPH  
Refoulement maximal  
de 5,5 mètres**

Idéale pour un  
**drainage automatique**  
des puits de  
sous-sol résidentiel

**CAPACITÉ DE LA POMPE**

TÊTE	LPH	GPH	US
18' 5,5m	900	225	
15' 4,5m	3475	925	
10' 3,0m	7675	2025	
5' 1,5m	11525	3050	

Pertes dues à la friction non incluses

**- SERIE PROFESSIONNELLE****Fonctionnement  
Départ - Arrêt  
AUTOMATIQUE**

- Boîtier fabriqué de fonte robuste
- Décharge de 1 1/2" avec adaptateur 1 1/4"
- Moteur refroidi à l'huile
- Câble électrique de 2.4m

Remplace les pompes submersibles  
ou à colonne et est conçue pour  
une installation permanente dans  
un bassin de 10" et plus.

**Évacuation d'eau**  
SYSTÈME DE POMPAGE[www.burcam.com](http://www.burcam.com)