



400401T

1/2 HP

### SUBMERSIBLE SEWAGE PUMP

Pumps up to 4900 US GPH  
Maximum Head of 25 Feet



2" solids handling capabilities

#### PUMP CAPACITY

HEAD	LPH	US GPH
25' 7,5m	2275	600
20' 6,0m	8325	2200
15' 4,5m	11350	3000
10' 3,0m	14765	3900
5' 1,5m	18550	4900

Friction loss in pipe not included



Automatic On - Off OPERATION

- Made of rugged cast iron
- Discharge of 2"
- Water-cooled motor
- 18' electrical cords

Replaces sewage pumps and designed for a permanent installation in a sewage basin.



Water out PUMP SYSTEM

www.burcam.com



**POMPE D'ÉGOUT  
SUBMERSIBLE**

Pompe jusqu'à 18550 LPH  
Refoulement maximal  
de 7,5 mètres



**ACCEPTÉ**  
les solides  
jusqu'à 2"

**CAPACITÉ DE LA POMPE**

TÊTE	LPH	GPH US
25' 7,5m	2275	600
20' 6,0m	8325	2200
15' 4,5m	11350	3000
10' 3,0m	14765	3900
5' 1,5m	18550	4900

Pertes dues à la friction non incluses



**Fonctionnement  
Départ - Arrêt  
AUTOMATIQUE**

- Fabriquée de fonte robuste
- Décharge de 2"
- Moteur refroidi à l'eau
- Câbles électriques de 5.5m

**Remplace les pompes d'égout  
et est conçu pour une installation  
permanente dans un bassin d'égout.**



Évacuation d'eau  
SYSTÈME DE POMPAGE

