



400405T

3/4 HP

SUBMERSIBLE SEWAGE PUMP

Pumps up to 4900 US GPH
Maximum Head of 25 Feet



PUMP CAPACITY

HEAD	LPH	US GPH
25' 7,5m	2200	600
20' 6,0m	5600	1500
15' 4,5m	9000	2400
10' 3,0m	12500	3300
5' 1,5m	18550	4900

Friction loss in pipe not included



Automatic On - Off OPERATION

- Made of cast iron and stainless steel for longevity
- Discharge of 2"
- Cast iron vortex impeller
- Oil-cooled motor
- 20' electrical cords

Replaces sewage pumps and designed for a permanent installation in a sewage basin.



Water out
PUMP SYSTEM

www.burcam.com



3/4 cv

POMPE D'ÉGOUT SUBMERSIBLE

Pompe jusqu'à 18550 LPH
Refoulement maximal
de 7,5 mètres



CAPACITÉ DE LA POMPE

TÊTE	LPH	GPH US
25' 7,5m	2200	600
20' 6,0m	5600	1500
15' 4,5m	9000	2400
10' 3,0m	12500	3300
5' 1,5m	18550	4900

Pertes dues à la friction non incluses



Fonctionnement Départ - Arrêt AUTOMATIQUE

- Fabriquée de fonte robuste et d'acier inoxydable pour une durabilité accrue
- Décharge de 2"
- Impulseur vortex en fonte
- Moteur refroidi à l'huile
- Câbles électriques de 6m

Remplace les pompes d'égout et est conçu pour une installation permanente dans un bassin d'égout.



Évacuation d'eau
SYSTÈME DE POMPAGE

www.burcam.com

