



400535

1/2 HP

SUBMERSIBLE SEWAGE PUMP

Pumps up to 5400 US GPH
Maximum Head of 20 Feet



2" solid
handling
capabilities

PUMP CAPACITY

HEAD	LPH	US GPH
20' 6,0m	1000	250
15' 4,5m	7900	2100
10' 3,0m	15150	4000
5' 1,5m	20500	5400

Friction loss in pipe not included



Automatic On - Off OPERATION

- Heavy duty type
- Pump body made of rugged cast iron
- 2" discharge
- Oil-cooled motor
- Vortex impeller, clog-free type, made of cast iron
- 8' electrical cords

Replaces sewage pumps and designed for a permanent installation in a sewage basin.



Water out
PUMP SYSTEM

www.burcam.com



**POMPE D'ÉGOUT
SUBMERSIBLE**

Pompe jusqu'à 20500 LPH
Refoulement maximal
de 6,0 mètres



ACCEPTÉ
les solides
jusqu'à 2"

CAPACITÉ DE LA POMPE

TÊTE	LPH	GPH US
20' 6,0m	1000	250
15' 4,5m	7900	2100
10' 3,0m	15150	4000
5' 1,5m	20500	5400

Pertes dues à la friction non incluses



**Fonctionnement
Départ - Arrêt
AUTOMATIQUE**

- De type service intense
- Pompe fabriquée de fonte robuste
- Décharge de 2"
- Moteur refroidi à l'huile
- Impulseur vortex, de type ouvert, fabriquée de fonte
- Câbles électriques de 2.4m

**Remplace les pompes d'égout
et est conçu pour une installation
permanente dans un bassin d'égout.**



Évacuation d'eau
SYSTÈME DE POMPAGE

www.burcam.com

