



506528S

1 HP

# SHALLOW WELL JET PUMP SYSTEM

Pumps up to 905 US GPH  
Maximum Suction Lift of 25 Feet



## PUMP CAPACITY

LIFT		LPH	US GPH
25'	7,5m	1325	350
20'	6,0m	1850	490
15'	4,5m	2460	650
10'	3,0m	2935	775
5'	1,5m	3425	905

Friction loss in pipe not included

**Stainless steel pump body and motor casing**



NPT Connection	1"	
Pressure switch set to	20/40	30/50
Precharge to	18 PSI	28 PSI
Drawdown	5.0 US GALLON	4.0 US GALLON

- Pump :** - 115/230 fan-cooled commercial motor with 30/50 pressure switch
- Built-in ejector
- Stainless steel mechanical seal
- Tank :** - No water-air contact in tank
- No water-tank contact
- Replaceable bladder pressure tank

**16 US gallon steel air pressure tank.**



Water in  
PUMP SYSTEM

www.burcam.com



**SYSTÈME DE POMPE À JET  
DE Puits DE SURFACE**

Pompe jusqu'à 3425 LPH

Aspiration verticale maximale  
de 7,5 mètres



**CAPACITÉ DE LA POMPE  
ÉLÉVATION LPH GPH US**

25' 7,5m	1325	350
20' 6,0m	1850	490
15' 4,5m	2460	650
10' 3,0m	2935	775
5' 1,5m	3425	905

Pertes dues à la friction non incluses

**Boîtier de pompe et  
moteur en acier inoxydable**



Branchement NPT	1"	
Interrupteur à pression réglé à	20/40	30/50
Préchargé à	18 LBS PO <sup>2</sup>	28 LBS PO <sup>2</sup>
Soutirage	5.0 Gallon US	4.0 Gallon US

**Pompe :** - Moteur commercial 115/230V refroidi par ventilateur avec interrupteur à pression 30/50

- Éjecteur intégré
- Sceau mécanique en acier inoxydable

**Réservoir :** - Aucun contact de l'eau avec l'air  
- Aucun contact de l'eau avec le réservoir  
- Réservoir à membrane remplaçable

**Comprend un  
réservoir de 60 L.**

