



300610FP

1/3 HP

SUBMERSIBLE SUMP PUMP

Pumps up to 2200 US GPH
Maximum Head of 20 Feet



PUMP CAPACITY

| HEAD | LPH | US GPH |
|----------|------|--------|
| 20' 6,0m | 4150 | 1100 |
| 15' 4,5m | 5700 | 1500 |
| 10' 3,0m | 7200 | 1900 |
| 5' 1,5m | 8325 | 2200 |

Friction loss in pipe not included



Automatic On - Off OPERATION

- Non-corrosive Noryl construction
- 1 1/4" discharge
- 8' electrical cord

Replaces upright and submersible pumps and designed for a permanent installation in a 10" basin and larger.



Water out
PUMP SYSTEM

www.burcam.com





300610FP

1/3 CV

POMPE DE PUISARD SUBMERSIBLE

Pompe jusqu'à 8325 LPH
Refoulement maximal
de 6,0 mètres



CAPACITÉ DE LA POMPE

| TÊTE | LPH | GPH | US |
|------|-----|-----|----|
|------|-----|-----|----|

| | | | |
|----------|------|------|--|
| 20' 6,0m | 4150 | 1100 | |
| 15' 4,5m | 5700 | 1500 | |
| 10' 3,0m | 7200 | 1900 | |
| 5' 1,5m | 8325 | 2200 | |

Pertes dues à la friction non incluses



**Fonctionnement
Départ - Arrêt
AUTOMATIQUE**

- Fabriquée de Noryl non corrosif
- Décharge de 1 1/4"
- Câble électrique de 2.4m

**Remplace les pompes submersible
ou à colonne et est conçue pour
une installation permanente dans
un bassin de 10" et plus.**



Évacuation d'eau
SYSTÈME DE POMPAGE

www.burcam.com

