



400424

3/4 HP

COMPLETE GRINDER PUMP KIT

Pumps up to 1875 US GPH
Maximum Head of 35 Feet

Basin model 450655 18" x 30"
Sewage lid model 450657

- Basic discharge pipe and
2" check valve included

PUMP CAPACITY

HEAD		LPH	US GPH
35'	10,5m	1900	500
30'	9,0m	4200	1100
20'	6,0m	6200	1635
10'	3,0m	7100	1875

Friction loss in pipe not included



2" NPT
discharge

- Vortex impeller, clog-free type, combined with a grinder to shred solids
- Pump and motor housing made of cast iron
- Bottom suction
- 115V, 60Hz motor, with automatic thermal and overload protection

**New grinding technology
for sewage application,
to grind solids.**



Water out
PUMP SYSTEM

www.burcam.com



3/4 cv

SYSTÈME DE POMPE BROYEUSE POUR ÉGOUT

Pompe jusqu'à 7100 LPH

Refoulement maximal
de 10,5 mètres

Bassin modèle 450655 18" x 30"
Couvercle de puisard modèle
450657

- Tuyau de décharge de base
et clapet de retenue 2" inclus

CAPACITÉ DE LA POMPE

TÊTE	LPH	GPH US
------	-----	--------

35' 10,5m	1900	500
30' 9,0m	4200	1100
20' 6,0m	6200	1635
10' 3,0m	7100	1875

Pertes dues à la friction non incluses



Décharge de
2" NPT

- Impulseur Vortex, de type ouvert, combiné avec un broyeur à solides
- Pompe et boîtier du moteur fabriquée de fonte
- Aspiration par le dessus
- Moteur 115V, 60Hz, muni de protection thermique et de surcharge

**Nouvelle technologie de déchiquetage
pour application d'égout pour éliminer
les solides.**



Évacuation d'eau
SYSTÈME DE POMPAGE

www.burcam.com

